NiMH Battery Charger (CHVCM4E/CHVCM4)

Download Instructions (Americas)
Download Instructions (Rest of World)

ENHANCED COMMUNICATION

- Multiple colored LED lights indicate charge status





BATTERY PROTECTION

- Limits damage to batteries from overcharge



SAFETY TIMER

- Ensures charger is not active for extended periods of time





Before Using Your Charger:
Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with *Energizer*® NiMH batteries.

Product Detail:

Designation: Value Charger / Maxi Charger
Model: CHVCM4E / CHVCM4
Color: Black
Charge Capability: "AA" (2) or (4) / "AAA" (2) or (4)
"AA" (2) and "AAA" (2) Simultaneously
Note: Please note battery orientation diagrams in the instructions.

Charging Times: (estimated)

Battery (NiMH)	Capacity (mAh)	Estimated (time)
AA	1300-2000	6-8 hrs
AA	2000-2300	8-10 hrs
AAA	500-800	5-7 hrs

Shutoff Mechanism: Delta V Detection
Timer Control: 11 hours
Charging Current: "AA" 260-300mA
"AAA" 120-150mA
Trickle Charge: None
Input Rating (US): 110-127VAC, 50-60Hz, 6W
Input Rating: 100-240VAC, 50-60Hz, 6W
Typical Weight: 107 grams
Dimensions (mm): 115 x 71 x 62 (H x L x W)
Safety Features: Reverse Polarity Protection
Bad Battery Detection
Primary Battery Detection
Delta V Charging Cut Off
Safety Timer to Prevent Overcharge

Important Notice
This datasheet contains information specific to products manufactured at the time of its publication.
Contents herein do not constitute a warranty.